E-FLITE® CLIPPED WING CUB

EFL5150 BNF BASIC
EFL5175 PNP



DIE GEHEIMWAFFE ALLER CUB-LIEBHABER

Die E-flite Clipped Wing Cub ist eine äußerst gut fliegende Symbiose aus einem echten Klassiker und sportlichem Allrounder. Die stabile Konstruktion glänzt mit liebevollen Scale Details und modernster elektronischer Unterstützung wie dem optionalen Safe Select System.

The E-flite® Clipped Wing Cub 1.2m park flyer captures the essence of the classic variant with inspiring versatility only possible with durable construction, abundant scale detail and state-of-the-art electronics such as SAFE® Select flight assistance.

	BNF BASIC PNP PLUG-N-PLAY AS3X
Spannweite / Wingspan	1250 mm
Länge / Length	985 mm
Tragflächeninhalt / Wing Area	26.2 dm²
Abfluggewicht / Flying Weight	1360g
Motor / Motor	10er Brushless Outrunner
Regler / ESC	40A Brushless
Akku / Battery	3S LiPo 2200-3000mAh



Art.Nr.	Bezeichnung / Description		
EFL5150 BNF Basic	E-flite Clipped Wing Cub 1.2m		
EFL5175 PNP			

FEATURES

- Stabilität und Präzision der AS3X Technologie (nur BNF Basic)
- Optionales SAFE® Select System (nur BNF Basic)
- High-power Brushless Motor mit 40A ESC
- Einteilige Tragfläche mit Composite Verstärkung
- Klappbare Aluminium Tragflächenstreben mit Schnellverschluss
- Scale Oberflächen- , Motor- und Propellerdetails
- Stoßgedämpftes Fahrwerk mit Scale Abdeckungen und Radschuhen
- 4-Kanal Kontrolle mit 4 eingebauten Microservos
- Leichte und stabile EPO Schaumkonstruktion
- Große vordere Klappe für einfachen Akkuwechsel
- Spektrum™ 6-Kanal DSMX® Technologie
- Schwimmerset optional

BENÖTIGT WIRD

- min. 5 Kanal DSMX®/DSM2 Fernsteuerung + Empfänger (PNP Version)
- 2200–3000mAh 3S LiPo (EFLB22003S30)
- LiPo Ladegerät

FEATURES

- Stability and precision of AS3X® technology
- Optional SAFE® Select flight envelope protection
- High-power brushless motor with a robust 40A ESC
- Simple one-piece wing features rigid composite reinforcement
- Fold-away aluminum struts with quick-release hardware and storage
- Intricate scale engine, propeller and surface detail
- Shock-absorbing landing gear with scale covers and wheel pants
- 4-channel control with four micro servos installed
- Lightweight and durable EPO foam construction
- Large front, top hatch makes battery changes simple
- Spektrum™ 6-channel receiver with industry-leading DSMX® technology (BNF Basic)
- Optional float set makes float plane conversion easy

NEEDED TO COMPLETE

- 5+ Channel DSMX®/DSM2® Transmitter + Receiver (PNP Version)
- 2200–3000mAh 3S LiPo (EFLB22003S30)
- LiPo Charger

www.modellmarkt24.ch; www.modellmarkt24.de